

Luftspule (HiFi-Anwendungen)

Spezifikationen

<i>Ausführung</i>	Rundspule
<i>Drahtstärke</i>	0,7 mm / 1,0 mm / 1,4 mm



Modelle

<i>Typ</i>	<i>mH</i>	<i>R-DC</i>	<i>Durchmesser (d)</i>	<i>Höhe (h)</i>	<i>Bauform</i>
11600	0,10	0,14	30 mm	17,5 mm	3
11601	0,15	0,17	30 mm	17,5 mm	3
11602	0,22	0,21	30 mm	17,5 mm	3
11603	2,70	0,90	58 mm	25 mm	6
11604	3,30	1,05	58 mm	25 mm	6
11605	0,33	0,26	40 mm	17,5 mm	4
11606	0,39	0,29	40 mm	17,5 mm	4
11607	0,47	0,32	40 mm	17,5 mm	4
11608	0,68	0,39	58 mm	15 mm	5
11609	0,82	0,44	40 mm	17,5 mm	4
11610	1,00	0,49	58 mm	15 mm	5
11611	1,20	0,54	58 mm	15 mm	5
11612	1,50	0,62	58 mm	15 mm	5
11613	1,80	0,70	58 mm	25 mm	6
11614	2,20	0,83	58 mm	25 mm	6
11615	0,10	0,23	25 mm	8 mm	1
11616	0,18	0,31	36 mm	8 mm	2
11617	0,39	0,51	36 mm	8 mm	2
11618	0,47	0,58	30 mm	17,5 mm	3
11619	0,68	0,70	30 mm	17,5 mm	3
11621	0,33	0,48	36 mm	8 mm	2
11622	0,56	0,55	30 mm	17,5 mm	3